JP 3041851

Patents Cited by Inventor: 0 Patents Cited by Examiner: 0

Citing Patents: 0

Articles Cited by Inventor: 0 Articles Cited by Examiner: 0

Patent Number(s):

JP3041851-B1; JP2001002774-A → ORIGINAL POCUMENT

Title

Polyester manufacturing method for film and sheet molding, involves carrying out water treatment of polyester tip in process chamber, with coater having specific range of hardness

Patent Assignee Name(s) and Code(s):

TOYO BOSEKI KK (TOYM) TOYOBO KK (TOYM)

Derwent Primary Accession Number:

2000-368524 [32]

Abstract:


NOVELTY - Water treatment of polyester tip in a process chamber, is carried out with water having total hardness of 0.01-30 CaCO3mg/l. The polyester tip is continuously supplied to the processing chamber and the treated water ejected from the chamber is recycled.

USE - For film and sheet molding performed for manufacture of bottle containers to store seasoning oil, beverages, cosmetics and detergents.

ADVANTAGE - Die stains during molding are prevented, as favorable polyester is obtained by water treatment.

DESCRIPTION OF DRAWING(S) - The figure shows the schematic view of polyester manufacturing apparatus.

Drawing:



International Patent Classification:

B29B-013/02; B29C-049/00; B29K-067:00; B29L-022:00; C08G-063/90; C08G-063/183

Derwent Class:

A23 (Polyamides, polyesters, polycarbonates, alkyds); A31 (Preliminary processes); A92 (Packaging and containers, ropes, nets)

Derwent Manual Code(s):

A05-E01C; A11-C03

Patent Number Publ. Date Main IPC Week Page Count Language JP3041851-B1 15 May 2000 C08G-063/90 200032 Pages: 7 JP2001002774-A 09 Jan 2001 C08G-063/90 200107 Pages: 7

Application Details and Date:

 JP3041851-B1
 JP174535
 21 Jun 1999

 JP2001002774-A
 JP174535
 21 Jun 1999

Priority Application Information and Date:

JP174535 21 Jun 1999